

PLASMA 40A CUTTER 40A











40A PFC Inverter Plasma Cutter

- ✓ IGBT Inverter Technology Smooth & stable output, increased reliability, high duty cycle
- ✓ Microprocessor Control System Superior & Dynamic Arc Characteristics
- ✓ Increased duty cycle and energy efficiency with active PFC technology
- ✓ Multi voltage input will operate with wide range of input voltage, can even be used with long extension leads
- ✓ Protected external air regulator with water trap/ filter Easy adjustment & serviceability
- ✓ Euro Connect System Safe and robust connection to machine
- Advanced Strata plasma torch with European torch head Enables superior cutting performance and long consumable life
- ✓ Non-HF Arc Starting System Increased reliability and low EMF pollution
- ✓ Automatic Pilot Arc Control System Increased cutting speed and capability, especially for discontinuous cutting
- ✓ Lightweight & Compact Design Ideal for portable applications
- ✓ Production tested with 440V Extreme stress testing in production for rugged reliability.
- ✓ Industrial IP23 casing with front panel protection Resistant to damage, moisture and corrosion
- High quality & over specified electronic components
- Intelligent Plasma Torch Protection System Protects plasma torch from damage from incorrect air pressure, consumables not in place, excessive pilot arc use.
- ✓ Intelligent Machine Protection System Temperature, voltage and current sensors for increased reliability & safety
- Generator Friendly Designed to work with generator power supply and protect from power surges.
- Air flow manual activation switch Set & test air pressure without the need to trigger the torch

Description	Details
DIMENSIONS (LxWxH)	510 x 146 x 278mm
WEIGHT	8kg
INPUT POWER SUPPLY	230V AC 15A 50/60Hz
INPUT POWER SUPPLY TOLERANCE	90 - 275V AC
MAXIMUM INPUT CURRENT	21A
GENERATOR CAPACITY	6KVA
PLASMA CURRENT OUTPUT	20 - 40V
DUTY CYCLE	40A@44% 30A@100%
PLASMA PRODUCTION CUT CAPACITY - CARBON STEEL	16mm
PLASMA PRODUCTION CUT Capacity - Aluminium	12mm
PLASMA SEVERANCE CUT - CARBON STEEL	16mm

Description	Details
INSULATION CLASS	IP23
COMPRESSED AIR REQUIREMENT	110L/min 5bar
POWER EFFICIENCY	80%
POWER FACTOR	0.99
STANDARDS	EN60974-1:2012
WARRANTY	48 Months

Includes:



4m Earth Lead

XT4000 60A





Optional:













PLASMA CUTTING ACCESSORIES & CONSUMABLES

O Standard Optional

ACCESSORY:	EZICUT40i	ADVANCECUT45	ADVANCECUT80	ADVANCECUT125
Earth Leads	○	○	○	○
	AEL1625	AEL3550	AEL1625	AEL3550
Plasma Torch	O	O	○	○
	17373	17373	XTY125-6X-CC	XTY125-6X-CC
Consumables Kit	◆	▼	●	●
	XT4000KIT	XT4000KIT	TH125KIT	TH125KIT
Machine Torch	-	-	● YM125-12-CC64	-

Automatic Welding Helmets

- ✓ Variable Shade
- Complete with batteries ready to go
- ✓ Suitable for automotive DIY and industrial use.

WT180	Variable Shade 9-13	
WT350	True Colour, 4 Sensor with grind function	
SV3000	True Colour, Shade 5 - 13 + Grind Function (MIG/TIG/MMA/Plasma)	
SV4000	Panoramic view with auto darkening side panels. Shade 4 - 13 + Grind Function (MIG/TIG/MMA/Plasma)	
DW7000XL	True Colour, with grinding visor. Shade 5 - 13 + PRSL Filtration System (MIG/TIG/MMA/Plasma)	



XT4000 Plasma Cutting Torch Consumables: Electrodes

CODE:	DESCRIPTION:
XT4003	Standard Electrode (XT4000)
XT4003-L	Extended Electrode (XT4000)

Cutting Tips

XT4005-08	8 0.8mm Cutting Tip, 20 - 30A (XT4000)	
XT4005-09	0.9mm Cutting Tip, 30 - 40A (XT4000)	
XT4005-08L 0.8mm Extended Cutting Tip, 20 - 30A (XT4000)		
XT4005-09L	0.9mm Extended Cutting Tip, 30 - 40A (XT4000)	

Other

XT4006	Gas Distributor (Swirl Ring) (XT4000)
XT4007	Retaining Cap (XT4000)
XT4008	Stand Off Guide (XT4000)







Premium Welding Gloves

- ✓ Fully lined
- ✓ Quality Hard-Wearing Leather
- ✓ One piece back✓ Special "comfort fit".

WT-AWG01	WT-AWG01 Black/Gold Gloves - Pair	
WT-AWG02	Red/Gold Gloves - Pair	
WT-TWG20	TIG Welding Gloves - Pair	

Strata Integrated Storage Trolley

- ✓ Pull out drawer
- ✓ 25.85kg, 920 x 420 x 450mm (L x W x H)

32673 Integrated Storage trolley



Extension Cord

- ✓ 28A rated cable / 100% duty cycle
- ✓ Suitable for any equipment on 15A plug

Heavy Duty Extension Cord, 15m - 3-Core, 2.5mm Cable w/ 15A plug & Socket

