

The K 2000-Series



One-piece Roto-Mold chassis
Virtually indestructible

Total-stop system
Auto-shutdown feature improves seal life-span and reduces power consumption

Tidy storage system
Practical stowing of the trigger gun with safety catch and lances

Heavy Duty
Non-marking Wheels

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank (TST design)

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task



2 YEAR
COMMERCIAL
WARRANTY

Brass
Pump Head
10 YEAR
WARRANTY



Technical specifications		K2160TST single phase	
Operating pressure adjustable	psi	2030	
Max. admissible overpressure	psi	2320	
Connected load	V / ~ / Hz / A	230 / 1 / 50 / 14	
Motor speed	Rpm	1400	
Water output	l/min l/h	11	660
kW		3.3	
Power supply cable	m	5	
Dimensions L x W x H	mm	335 / 375 / 980	
Weight	kg	41	
Detergent Injector		●	
Equipment			
Hose drum		●	
Steel braided high-pressure hose	m	15	
Trigger gun with safety catch	Model	M2000	
Dirtkiller lance	Nozzle size	● 042	
Vario-Jet lance	Nozzle size	● 042	

